

TSUNAMI ROVE

The Rove offers an easy-to-operate Regenerative Drying System optimized for portability in any application.

- 1 10Hp Regenerative Dryer with "lift-off" design
- 2 Pre-filtration
 - 1st Stage Water Separator
 - 2nd Stage Oil Coalescing Filter
- 3 Solenoid Valve Time - OR- Pneumatic Generator
- 4 30 Gal Receiver Tank on wheels
- 5 High Flow Piston Outlet Regulator

Simply plug your air connection into the Tsunami pre-filters and you're ready to go! The Rove provides your shop with portable versatility by giving you the cleanest, driest compressed air available whenever and wherever needed.

The Rove system incorporates industry leading Tsunami drying technology packaged as a complete system. The systems includes a water separator, oil coalescing filter and automatic float drains to assure proper draining of water, oil and other contaminants. The system is mounted on a 30 gallon receiver tank to provide mobility and storage of clean, dry air.

New Cut the cord! The Tsunami Rove is now available with a pneumatic generator power supply. Pneumo powered models operate by consuming approximately 1-2 scfm from the dryer.

FEATURES & BENEFITS

- Wide track tires provide 100% portability
- Compact design with "lift-off" regenerative dryer allows system to be stored or transported anywhere
- Low relative humidity - down to .01% RH
- Dew points down to -80°F
- Easy, low-cost maintenance - under \$100/yr average
- Waterborne and Solvent ready!
- Pneumatically powered model provides unmatched versatility



Part Number	Power	Max Flow	Port Size	Weight	Dimensions (HWD)
21999-0945	120v	40 scfm	1/2" npt	150 lbs	4½' x 2' x 2'
21999-0945-PP	Pneumo Gen	40 scfm	1/2" npt	150 lbs	4½' x 2' x 2'

